

Innovation + Quality

Valves, controls + systems

Thermostats "**vindo** TH" and "**vindo** TD" Product range



oventrop

Thermostats "vindo TH" and "vindo TD"



The thermostats "vindo TH" (connection thread M 30 x 1.5) and "vindo TD" (squeeze connection) with liquid sensor serve to control the room temperature.

The thermostats with their new, slim design and reduced dimensions combine exclusive form with high functional efficiency.

The operation and optical display are excellent. The nominal values are easily set. Where there is insufficient lighting or for visually handicapped persons, the basic setting "3" can be easily found with the help of the tactile setting devices.

The thermostat is elegant due to its balanced forms. The lines are clear and smooth.

The collar nut of the "vindo TH" is nickel plated and that of the "vindo TD" is made of white plastic, RAL 9016.

The handgrip is white (RAL 9016), the lower central piece is black.

	ltem	Packing unit	ltem no.	Information	
	Thermostat "vindo тн" with liquid sensor Connection thread M 30 x 1.5			Max. heating water temperature: 120°C.	
<u>-рбс</u>	white model	(10)	101 30 66	With '0' setting, temperature range 7-28°C graduation on cap 0 * 1-5	e from
	Thermostat "vindo тр" with liquid sensor Squeeze connection				Printed on paper free from chlorine bleaching.
	white model	(10)	101 30 76	With '0' setting, temperature range 7-28°C graduation on cap 0 % 1-5	Product range 1 PR 235-1/2/04.2011/DD
Further information				OVENTROP GmbH & Co. KG Paul-Oventrop-Straße 1	Prodi PR 2

the Oventrop catalogue "Products" and on the internet, product range 1

Subject to technical modification without notice.

Paul-Oventrop-Straße 1 D-59939 Olsberg Germany Telephone +49 (0) 29 62 82-0 Telefax +49 (0) 29 62 82-450 E-Mail mail@oventrop.de Internet www.oventrop.de